

规格 (直径×长度) Specification (D×W)	筒体转速	装球量	进料粒度	出料粒度	产量	电机功率	重量
	(r/min)	(t)	(mm)	(mm)	(t/h)	(kw)	(t)
Φ1830×3000	26.3	14.4	≤25	0.074-0.3	4-10	130	35.5
Φ1830×4500	25.5	20	≤25	0.074-0.3	7.3-17.2	180	38.9
Φ1830×6400	24.1	21	≤25	0.074-0.3	6.5-15	210	34
Φ1830×7000	24.1	23	≤25	0.074-0.3	7.5-17	245	36
Φ2100×3000	24.35	19.8	≤25	0.074-0.3	5.8-14	210	57.3
Φ2100×3600	23.8	28	≤25	0.074-0.3	6.2-36	210	65.4
Φ2100×4500	23.7	24	≤25	0.074-0.3	8-43	245	42
Φ2100×7000	23.7	26	≤25	0.074-0.3	8-48	280	50
Φ2200×3000	24.35	21	≤25	0.074-0.3	7.5-16	210	59.5
Φ2200×4500	21.5	27	≤25	0.074-0.3	9-45	280	48.5
Φ2200×7000	21.7	35	≤25	0.074-0.3	15-28	380	54
Φ2400×2400	20.8	20.7	≤25	0.074-0.3	7.0-14	210	53.3
Φ2400×3000	21.6	25.8	≤25	0.074-0.3	7.8-18	245	59.2
Φ2700×2100	21.7	23	≤25	0.074-0.3	8.5-17	260	67.4
Φ2700×4000	20.7	40	≤25	0.074-0.3	12-80	400	94
Φ3200×3600	18.6	56.5	≤25	0.074-0.3	8.6-39.6	63	145
Φ3600×4500	17.8	38	≤25	0.074-0.3	29-61	1250	200
Φ3600×6000	17.8	117	≤25	0.074-0.3	35-73	1600	230
Φ4000×5000	16.4	101	≤25	0.074-0.3	48-97	1600	260